

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 7/00	A2	(11) International Publication Number: WO 99/32070 (43) International Publication Date: 1 July 1999 (01.07.99)
(21) International Application Number: PCT/EP98/08149 (22) International Filing Date: 10 December 1998 (10.12.98) (30) Priority Data: 9726969.0 19 December 1997 (19.12.97) GB (71) Applicant (for AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). (71) Applicant (for all designated States except AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL). (71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165-166 Backbay Reclamation, Mumbai 400 020 (IN).		(72) Inventors: COUPE, Serge, Aime, Patrick; c/o Elida Faberge, Usine de Laboratoires de Compiègne, Zone Industrielle, Boîte postale 139, F-60881 Le Meux Cedex (FR). REID, Euan, Stuart; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside L63 3JW (GB). STEER, David, Charles; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside L63 3JW (GB). (74) Agent: GRIFFITHS, Sarah, Helen; Unilever plc, Patent Dept., Colworth House, Sharnbrook, Bedford MK44 1LQ (GB). (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: MOUSSE-FORMING SHAMPOO COMPOSITIONS (57) Abstract A mousse-forming cleansing shampoo composition having improved conditioning performance comprising: (A) a foamable concentrate comprising: (i) at least one surfactant; (ii) emulsified particles of a conditioning agent having a particle size of ≤ 1 micron; (iii) a deposition polymer for the emulsified particles; (iv) an aqueous carrier; and (B) an aerosol propellant.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MOUSSE-FORMING SHAMPOO COMPOSITIONS

5 FIELD OF THE INVENTION

The present invention relates to mousse-forming shampoo compositions. More particularly, the invention relates to
10 mousse-forming shampoo compositions which include emulsified particles of a conditioning agent such as a silicone and which impart good conditioning benefits to hair and/or skin.

BACKGROUND AND PRIOR ART

15

Mousses are a particularly convenient and pleasant-to-use product form for hair treatment formulations. The product is generally applied to the user's hand, where it forms a creamy foam which can be easily worked through the hair.

20

Such mousses have found widespread use in the context of hair styling products. The conventional hair styling mousse generally utilises a water soluble hair styling polymer, water, possibly a conditioning agent, an emulsifier,
25 aesthetic agents and an aerosol propellant. The mousse is typically applied to hair dampened with water, spread through the hair and allowed to dry, giving a temporary set which can be removed by water or by shampooing.

30

It would be desirable to provide a rinse-off surfactant-based cleansing shampoo in a mousse product form. Consumers

- 2 -

appreciate the ease of dispensing and application of a
mousse, and the way it can be worked through the hair
without getting into the eyes. The latter would be
particularly advantageous in the context of formulations
5 based primarily on cleansing surfactants which can sometimes
be harsh and irritating to the eyes.
However, prior art systems of this type have not achieved
much success, largely because the level of conditioning they
deliver is insufficient for many people.

10

The problem stems mainly from the fact that the shampoo in
the dispenser must dispense easily. This requirement is
generally incompatible with shampoos which incorporate
conditioning agents.

15

For example, silicones are highly desirable conditioning
agents for incorporation into shampoos, as is well
documented in the literature. However, the problem arises
that the usual viscosity level required of the shampoo base
20 in order to prevent the silicone from separating in the
formulation is generally too high for effective dispensing
of the shampoo from an aerosol formulation. This is manifest
as a dispensing problem - the product will tend to dispense
slowly and unevenly.

25

We have now found that rinse-off surfactant-based cleansing
shampoo compositions can be formulated which deliver
excellent conditioning performance from a mousse product
form.

30

- 3 -

US 5,085,857 describes a hair shampoo incorporating a pre-formed aqueous emulsion of a silicone oil, in which the silicone is incorporated with a small particle size, less than 2 microns. The shampoos preferably contain a shear
5 thinning polymer or crystalline suspending agent to enhance stability.

EP A 0 529 883 and EP A 0 674 898 disclose hair shampoos comprising a microemulsified silicone oil in combination
10 with a cationic deposition polymer. The shampoo compositions are stated to have good mechanical stability, high optical transparency or translucency and excellent conditioning ability.

15 None of these publications disclose or suggest that an emulsified conditioning agent such as a silicone can be utilised in a propellant-driven system such as a mousse-forming product.

20 SUMMARY OF THE INVENTION

The present invention provides a mousse-forming cleansing shampoo composition having improved conditioning performance comprising:

25

(A) a foamable concentrate comprising:

(i) at least one surfactant;

- 4 -

(ii) emulsified particles of a conditioning agent having a particle size of \leq 1 micron;

(iii) a deposition polymer for the emulsified particles;

5

(iv) an aqueous carrier; and

(B) an aerosol propellant.

10 **DETAILED DESCRIPTION AND PREFERRED EMBODIMENTS**

Foamable Concentrate

15 The mousse-forming cleansing shampoo composition of the invention comprises a foamable concentrate and an aerosol propellant. The term "concentrate" will be used to refer to the liquid component of the shampoo composition other than the propellant. The term "mousse", as used herein, is the same as foam, and refers to the dispensed product unless
20 otherwise specified.

In general, for optimum dispensability of the product, we have found that the viscosity of the foamable concentrate should not exceed 3000 cps.

25

The viscosity of the foamable concentrate suitably ranges from 1 to 3000, preferably from 10 to 2000, ideally from 100 to 1000 cps.

- 5 -

Viscosity is measured in the conventional manner using a rotary viscometer (Brookfield Viscometer, LVT type, Rotor No.3, 12 rpm after 30 sec. at 25 degrees C).

5 In order to achieve such suitable viscosities as described above for the foamable concentrate, it is particularly preferred that the foamable concentrate be substantially free of crystalline suspending agents. By "substantially free" it is generally meant that the level of such agents be
10 about 0.5% or less, preferably about 0.1% or less, ideally no more than about 0.05% by weight of the foamable concentrate.

Crystalline suspending agents include long chain (e.g. C8-
15 C22) acyl derivative materials and long chain amine oxides, such as ethylene glycol long chain esters, alkanolamides of long chain fatty acids, long chain esters of long chain fatty acids, glyceryl long chain esters, long chain esters of long chain alkanolamides, and long chain alkyl dimethyl
20 amine oxides. Common suspending agents of this type are ethylene glycol esters of C14-C22 fatty acids (e.g. ethylene glycol distearate), C16-C22 fatty acid alkanolamides (e.g. stearic monoethanolamide, stearic monoisopropanolamide), C16-C22 alkyl dimethyl amine oxides and N,N-dihydrocarbyl
25 (C12-C22) amidobenzoic acid and salts thereof.

It may in some cases also be preferable, in order to achieve suitable viscosities as described above for the foamable concentrate, to incorporate therein a rheology modifier such
30 as a thinner. Suitable thinners include polyethylene glycol

- 6 -

(PEG), polypropylene glycol (PPG), sodium xylene sulphonate, sodium toluene sulphonate and urea. Preferred thinners are PEG 400 and PPG 400.

5 Conditioning Agent

The foamable concentrate comprises emulsified particles of a conditioning agent having a particle size of ≤ 1 micron.

10 It is particularly preferred that the conditioning agent is in the form of microemulsified particles. Typically such microemulsified particles will have a particle size of ≤ 0.15 microns, suitably from 0.01 to 0.15 microns.

15 Particle size may be measured by means of a laser light scattering technique, using a 2600D Particle Sizer from Malvern Instruments.

As used herein, the term "conditioning agent" includes any
20 material which is used to give a particular conditioning benefit to hair and/or skin. For example, in shampoo compositions for use on the skin, materials such as moisturisers, essential oils, sun-protective or after-sun treatment materials, occlusive oils and the like may be
25 used. In shampoo compositions for use on the hair, suitable materials are those which deliver one or more benefits relating to shine, softness, combability, wet-handling, anti-static properties, protection against damage, body, volume, stylability and manageability.

- 7 -

Preferred conditioning agents for use in the present invention include silicones. Suitable silicones may be one or more polyalkyl siloxanes, one or more polyalkylaryl siloxanes, or mixtures thereof. The silicone is insoluble
5 in the aqueous matrix of the composition and so is present as dispersed particles, in an emulsified form.

The viscosity of the silicone itself (not the emulsion or the final shampoo composition) preferably ranges from 10,000
10 cps to 5 million cps.

Suitable polyalkyl siloxanes include polydimethyl siloxanes which have the CTFA designation dimethicone, having a viscosity of up to 100,000 centistokes at 25 degrees C.
15 These siloxanes are available commercially from the General Electric Company as the Viscasil series and from Dow Corning as the DC 200 series. The viscosity can be measured by means of a glass capillary viscometer as set out further in Dow Corning Corporate Test Method CTM004 July 20 1970.

20

Also suitable is polydiethyl siloxane.

Also suitable are silicone gums, such as those described in US Pat. No. 4,152,416 (Spitzer), and on General Electric
25 Silicone Rubber product Data Sheet SE 30, SE 33, SE 54 and SE 76. "Silicone gum" denotes polydiorganosiloxanes having a molecular weight of from 200,000 to 1,000,000 and specific examples include polydimethyl siloxane polymers, polydimethyl siloxane/diphenyl/methylvinylsiloxane

- 8 -

copolymers, polydimethylsiloxane/methylvinylsiloxane
copolymers and mixtures thereof.

Aminofunctional silicones which have the CTFA designation
5 amodimethicone, are also suitable for use in the
compositions of the invention, as are polydimethyl siloxanes
having hydroxyl end groups (which have the CTFA designation
dimethiconol).

10 Various methods of making microemulsions of particles of
silicones for use in the invention are available and are
well known and documented in the art.

One particularly preferred technique for making silicone
15 microemulsions is that described in EP-A-228575.

In that document there is described a method of making a
stable microemulsion of high molecular weight silicone
polymer and water by sequentially adding at an effective
20 rate a standard emulsion comprising polydiorganosiloxane
precursor, surfactant and water to a polymerization catalyst
medium while mixing to form a clear, stable aqueous
microemulsion of polydiorganosiloxane.

25 Another method of making suitable microemulsions for use in
the invention are described in EP-A-0 138 192.

Alternatively, suitable microemulsions for use in the
invention are commercially available in a pre-
30 microemulsified form. This is particularly preferred since

- 9 -

the pre-formed microemulsion can be incorporated into the foamable concentrate by simple mixing. Examples of suitable pre-formed microemulsions include microemulsions DC2-1865, DC2-1870, and DC2-1391, all available from Dow Corning.

5 These are all microemulsions of dimethiconol.

The amount of silicone incorporated into the shampoo compositions of the invention depends on the level of conditioning desired and the material used. A preferred
10 amount is from 0.01 to about 10% by weight of the foamable concentrate although these limits are not absolute. The lower limit is determined by the minimum level to achieve conditioning and the upper limit by the maximum level to avoid making the hair and/or skin unacceptably greasy. We
15 have found that an amount of silicone of from 0.5 to 1.5% by weight of the foamable concentrate, is a particularly suitable level.

A further preferred class of conditioning agents are hair
20 body and volume enhancing materials. Examples are cross-linked silicone gums and per-alk(en)yl hydrocarbon materials.

Suitable cross-linked silicone gums are described in WO
25 96/31188. A preferred example is the material available from Dow Corning as DC X2-1787.

EP 567 326 and EP 498 119 describe suitable peralk(en)yl hydrocarbon materials for imparting stylability and enhanced
30 body to hair. Preferred materials are polyisobutylene

- 10 -

materials available from Presperse, Inc. under the PERMETHYL trade name.

The amount of hair body and volume enhancing material
5 incorporated into the shampoo compositions of the invention depends on the level of enhancement desired and the material used. A preferred amount is from 0.01 to about 10% by weight of the foamable concentrate although these limits are not absolute. The lower limit is determined by the minimum
10 level to achieve the body and volume enhancing effect and the upper limit by the maximum level to avoid making the hair unacceptably stiff. We have found that an amount of hair body and volume enhancing material of from 0.1 to 2% by weight of the foamable concentrate, is a particularly
15 suitable level.

Surfactant

The foamable concentrate comprises one or more surfactants,
20 to provide a cleansing benefit. Surfactant will also be present as emulsifier for the microemulsified particles of silicone.

Further surfactant(s) will be present as an additional
25 cleansing ingredient if sufficient for cleansing purposes is not provided as the emulsifier for the microemulsified particles of silicone. This further cleansing surfactant may be the same surfactant as the emulsifier, or may be different.

30

- 11 -

Suitable emulsifiers are well known in the art and include anionic and nonionic surfactants. Examples of anionic surfactants used as emulsifiers for the silicone particles are alkylarylsulphonates, e.g., sodium dodecylbenzene
5 sulphonate, alkyl sulphates e.g., sodium lauryl sulphate, alkyl ether sulphates, e.g., sodium lauryl ether sulphate nEO, where n is from 1 to 20 alkylphenol ether sulphates, e.g., octylphenol ether sulphate nEO where n is from 1 to 20, and sulphosuccinates, e.g., sodium
10 dioctylsulphosuccinate.

Examples of nonionic surfactants used as emulsifiers for the silicone particles are alkylphenol ethoxylates, e.g., nonylphenol ethoxylate nEO, where n is from 1 to 50, alcohol
15 ethoxylates, e.g., lauryl alcohol nEO, where n is from 1 to 50, ester ethoxylates, e.g., polyoxyethylene monostearate where the number of oxyethylene units is from 1 to 30.

Cleansing surfactants are typically selected from anionic,
20 nonionic, amphoteric and zwitterionic surfactants, and mixtures thereof.

Suitable anionic cleansing surfactants for shampoo compositions of the invention include the alkyl sulphates,
25 alkyl ether sulphates, alkaryl sulphonates, alkanoyl isethionates, alkyl succinates, alkyl sulphosuccinates, N-alkoyl sarcosinates, alkyl phosphates, alkyl ether phosphates, alkyl ether carboxylates, alpha-olefin sulphonates and acyl methyl taurates, especially their
30 sodium, magnesium ammonium and mono-, di- and

- 12 -

triethanolamine salts. The alkyl and acyl groups generally contain from 8 to 18 carbon atoms and may be unsaturated. The alkyl ether sulphates, alkyl ether phosphates and alkyl ether carboxylates may contain from one to 10 ethylene oxide
5 or propylene oxide units per molecule, and preferably contain 2 to 3 ethylene oxide units per molecule.

Examples of suitable anionics include sodium lauryl sulphate, sodium lauryl ether sulphate, ammonium lauryl
10 sulphosuccinate, ammonium lauryl sulphate, ammonium lauryl ether sulphate, sodium dodecylbenzene sulphonate, triethanolamine dodecylbenzene sulphonate, sodium cocoyl isethionate, sodium lauroyl isethionate, and sodium N-lauryl sarcosinate.

15 Nonionic cleansing surfactants suitable for use in shampoo compositions of the invention may include condensation products of aliphatic (C_6-C_{18}) primary or secondary linear or branched chain alcohols or phenols with alkylene oxides,
20 usually ethylene oxide and generally having from 6 to 30 ethylene oxide groups. Other suitable nonionics include alkylpolyglycosides and mono- or di-alkyl alkanolamides. Examples of the latter nonionics include coco mono- or di-ethanolamide and coco mono-isopropanolamide.

25 Amphoteric and zwitterionic cleansing surfactants suitable for use in compositions of the invention may include alkyl amine oxides, alkyl betaines, alkyl amidopropyl betaines, alkyl sulphobetaines (sultaines), alkyl glycinate, alkyl
30 carboxyglycinates, alkyl amphopropionates,

- 13 -

alkylamphoglycinates and alkylamidopropyl hydroxysultaines. Examples include lauryl amine oxide, cocodimethyl sulphopropyl betaine and preferably lauryl betaine, cocamidopropyl betaine and sodium cocamphopropionate.

5

The total amount of surfactant (including that used as emulsifier for the microemulsified particles of high viscosity silicone) is generally from 3 to 50% by weight, preferably from 5 to 30%, more preferably from 10% to 25% by weight of the foamable concentrate.

Deposition polymer

The foamable concentrate contains a deposition polymer for the microemulsified particles of silicone. By "deposition polymer" is meant an agent which enhances deposition of the particles of silicone from the shampoo composition of the invention onto the intended site during use, i.e. the hair and/or the scalp.

20

The deposition polymer may be a homopolymer or be formed from two or more types of monomers. The molecular weight of the polymer will generally be between 5 000 and 10 000 000, typically at least 10 000 and preferably in the range 100 000 to about 2 000 000. The polymers will have cationic nitrogen containing groups such as quaternary ammonium or protonated amino groups, or a mixture thereof.

25

The cationic charge density of the deposition polymer, which is defined as the reciprocal of the molecular weight of a

30

- 14 -

monomeric unit of the polymer containing one charge, should typically be at least 0.1 meq/g, preferably above 0.8 or higher. The cationic charge density should typically not exceed 4 meq/g. It is preferably less than 3 and more preferably less than 2 meq/g. The charge density can be measured using conductimetric analysis and should be within the above limits at the desired pH of use, which will in general be from about 3 to 9 and preferably between 4 and 8.

- 10 The cationic nitrogen-containing group will generally be present as a substituent on a fraction of the total monomer units of the deposition polymer. Thus when the polymer is not a homopolymer it can contain spacer non-cationic monomer units. Such polymers are described in the CTFA Cosmetic
15 Ingredient Directory, 3rd edition. The ratio of the cationic to non-cationic monomer units is selected to give a polymer having a cationic charge density in the required range.

- Suitable cationic deposition polymers include, for example,
20 copolymers of vinyl monomers having cationic amine or quaternary ammonium functionalities with water soluble spacer monomers such as (meth)acrylamide, alkyl and dialkyl (meth)acrylamides, alkyl (meth)acrylate, vinyl caprolactone and vinyl pyrrolidine. The alkyl and dialkyl substituted
25 monomers preferably have C1-C7 alkyl groups, more preferably C1-3 alkyl groups. Other suitable spacers include vinyl esters, vinyl alcohol, maleic anhydride, propylene glycol and ethylene glycol.

- 15 -

The cationic amines can be primary, secondary or tertiary amines, depending upon the particular species and the pH of the composition. In general secondary and tertiary amines, especially tertiary, are preferred.

5

Amine substituted vinyl monomers and amines can be polymerized in the amine form and then converted to ammonium by quaternization.

- 10 Suitable cationic amino and quaternary ammonium monomers include, for example, vinyl compounds substituted with dialkyl aminoalkyl acrylate, dialkylamino alkylmethacrylate, monoalkylaminoalkyl acrylate, monoalkylaminoalkyl methacrylate, trialkyl methacryloxyalkyl ammonium salt,
- 15 trialkyl acryloxyalkyl ammonium salt, diallyl quaternary ammonium salts, and vinyl quaternary ammonium monomers having cyclic cationic nitrogen-containing rings such as pyridinium, imidazolium, and quaternized pyrrolidine, e.g., alkyl vinyl imidazolium, alkyl vinyl pyridinium, and alkyl vinyl
- 20 pyrrolidine salts. The alkyl portions of these monomers are preferably lower alkyls such as the C1-C3 alkyls, more preferably C1 and C2 alkyls.

- Suitable amine-substituted vinyl monomers for use herein
- 25 include dialkylaminoalkyl acrylate, dialkylaminoalkyl methacrylate, dialkylaminoalkyl acrylamide, and dialkylaminoalkyl methacrylamide, wherein the alkyl groups are preferably C1-C7 hydrocarbyls, more preferably C1-C3, alkyls.

30

- 16 -

The deposition polymer can comprise mixtures of monomer units derived from amine- and/or quaternary ammonium-substituted monomer and/or compatible spacer monomers.

5 Suitable deposition polymers include, for example: cationic copolymers of 1-vinyl-2-pyrrolidine and 1-vinyl-3-methyl-imidazolium salt (e.g., Chloride salt) (referred to in the industry by the Cosmetic, Toiletry, and Fragrance Association, "CTFA". as Polyquaternium-16); copolymers of 1-
10 vinyl-2-pyrrolidine and dimethylaminoethyl methacrylate (referred to in the industry by CTFA as Polyquaternium-11); cationic diallyl quaternary ammonium-containing polymers including, for example, dimethyldiallylammonium chloride homopolymer (referred to in the industry (CTFA) as
15 Polyquaternium 6); mineral acid salts of amino-alkyl esters of homo-and co-polymers of unsaturated carboxylic acids having from 3 to 5 carbon atoms, as described in U.S. Patent 4,009,256; and cationic polyacrylamides as described in UK Application No. 9403156.4.

20

Other cationic deposition polymers that can be used include cationic guar gum derivatives, such as guar hydroxypropyltrimonium chloride (Commercially available from Celanese Corp. in their JAGUAR trademark series).

25

Examples are JAGUAR C13S, which has a low degree of substitution of the cationic groups and high viscosity. JAGUAR C15, having a moderate degree of substitution and a low viscosity, JAGUAR C17 (high degree of substitution, high
30 viscosity), JAGUAR C16, which is a hydroxypropylated cationic

- 17 -

guar derivative containing a low level of substituent groups as well as cationic quaternary ammonium groups, and JAGUAR 162 which is a high transparency, medium viscosity guar having a low degree of substitution.

5

Preferably the deposition polymer is selected from cationic polyacrylamides and cationic guar derivatives. Particularly preferred deposition polymers are JAGUAR C13S with a cationic charge density of 0.8meq/g. Other particularly
10 suitable materials include JAGUAR C15, JAGUAR C17 and JAGUAR C16 and JAGUAR C162.

The deposition polymer may be present in an amount of from about 0.01 to about 10% by weight of the total composition,
15 preferably from about 0.01 to about 1% by weight, more preferably from about 0.04 to about 0.5% by weight of the foamable concentrate.

Aqueous carrier

20

The foamable concentrate comprises an aqueous carrier, water forming the basis of the continuous phase of the microemulsion of particles of silicone conditioning agent. Water is generally present in an amount of from about 20 to
25 about 99% by weight of the foamable concentrate.

Propellant

Shampoo compositions of the invention contain an aerosol
30 propellant (B). This agent is responsible for expelling the

- 18 -

other materials from the container and forming the mousse character.

The propellant gas can be any liquefiable gas conventionally
5 used for aerosol containers. Examples of suitable
propellants include dimethyl ether, propane, n-butane and
isobutane, used singly or admixed. Other examples of
propellants are nitrogen, carbon dioxide, compressed air and
fluorohydrocarbons such as the material sold by Du Pont
10 under the trade name DYMEL 152a.

The amount of the propellant gases is governed by normal
factors well known in the aerosol art. For mousses the
level of propellant is generally from about 3 to about 15%,
15 optimally from about 4 to about 10% for creamy foam and good
sensory feel.

Optional Ingredients

20 Compositions of this invention may contain any other
ingredient normally used in hair treatment formulations.
These other ingredients may include hair styling resins,
colouring agents, antifoam agents, proteins, moisturising
agents, antioxidants, fragrances, antimicrobials and
25 sunscreens. Each of these ingredients will be present in an
amount effective to accomplish its purpose.

- 19 -

Packaging

Compositions of the invention are typically prepared by charging a suitable pressurisable container with the
5 foamable concentrate, then sealing the container and charging it with propellant (B) according to conventional techniques.

The invention will now be illustrated by the following non-
10 limiting examples.

All parts, percentages and proportions referred to are by weight unless otherwise indicated.

15 EXAMPLES

The following Examples illustrate mousse-forming shampoo compositions according to the present invention.

20 Example 1

A foamable concentrate was made up having the following formulation:

25

30

- 20 -

wt%	Ingredient	Chemical Name
9.0%	SLES 2EO	Sodium lauryl ether sulphate (2EO)
4.0%	CAPB	Cocamidopropylbetaine
4.0%	Laureth-7	Polyethylene glycol (7) ether of lauryl alcohol
3.2%	DC2-1391	Cross-linked dimethiconol (25% microemulsion, ex Dow Corning)
2.0%	PPG 400	Polyoxypropylene (9)
0.5%	Sodium benzoate	
0.5%	Fragrance	
0.3%	Polymer JR400	Polyquaternium-10
to 100%	deionised water	

5

The foamable concentrate was formulated into an aerosol mousse using 93 parts of the foamable concentrate and 7 parts CAP 40 (butane, 2.7 bar).

- 21 -

Example 2

A foamable concentrate was made up having the following formulation:

5

wt%	Ingredient	Chemical Name
14.0%	SLES 2EO	Sodium lauryl ether sulphate (2EO)
3.0%	DCX2-1787	Emulsion polymerised dimethiconol containing 0.6% cross-linking, (55% aqueous emulsion, ex Dow Corning)
2.0%	CAPB	Cocamidopropylbetaine
2.0%	PPG 400	Polyoxypropylene (9)
0.5%	Sodium benzoate	
0.5%	Fragrance	
0.05%	JAGUAR C13S	Guar hydroxypropyltrimonium chloride
to 100%	deionised water	

The foamable concentrate was formulated into an aerosol
10 mousse using 93 parts of the foamable concentrate and 7
parts CAP 40 (butane, 2.7 bar).

- 22 -

CLAIMS

1. A mousse-forming cleansing shampoo composition having improved conditioning performance comprising:

5

(A) a foamable concentrate comprising:

(i) at least one surfactant;

10 (ii) emulsified particles of a conditioning agent having a particle size of ≤ 1 micron;

(iii) a deposition polymer for the emulsified particles;

15 (iv) an aqueous carrier; and

(B) an aerosol propellant.

2. A composition according to claim 1, in which the foamable
20 concentrate is substantially free of crystalline suspending agents.

3. A composition according to claim 1 or claim 2, in which the foamable concentrate further comprises a rheology
25 modifier selected from the group consisting of polyethylene glycol (PEG), polypropylene glycol (PPG), sodium xylene sulphonate, sodium toluene sulphonate and urea.

4. A composition according to any preceding claim, in which
30 the conditioning agent is pre-microemulsified dimethiconol.

- 23 -

5. A composition according to any of claims 1 to 3, in which the conditioning agent is a cross-linked silicone gum or a per-alk(en)yl hydrocarbon material.

5

6. A composition according to any preceding claim, in which the total amount of surfactant (including that used as emulsifier for the microemulsified particles of high viscosity silicone) is from 10% to 25% by weight of the

10 foamable concentrate.

7. A composition according to any preceding claim, in which the deposition polymer is selected from the group consisting of cationic polyacrylamides and cationic guar derivatives.

15

8. A composition according to any preceding claim, in which the propellant gas is selected from the group consisting of dimethyl ether, propane, n-butane, isobutane and mixtures thereof.

20

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 7/50, 7/00	A3	(11) International Publication Number: WO 99/32070 (43) International Publication Date: 1 July 1999 (01.07.99)
(21) International Application Number: PCT/EP98/08149 (22) International Filing Date: 10 December 1998 (10.12.98) (30) Priority Data: 9726969.0 19 December 1997 (19.12.97) GB (71) Applicant (for AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). (71) Applicant (for all designated States except AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL). (71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165-166 Backbay Reclamation, Mumbai 400 020 (IN).		(72) Inventors: COUPE, Serge, Aime, Patrick; c/o Elida Faberge, Usine de Laboratoires de Compiègne, Zone Industrielle, Boite postale 139, F-60881 Le Meux Cedex (FR). REID, Euan, Stuart; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside L63 3JW (GB). STEER, David, Charles; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside L63 3JW (GB). (74) Agent: GRIFFITHS, Sarah, Helen; Unilever plc, Patent Dept., Colworth House, Sharnbrook, Bedford MK44 1LQ (GB). (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 10 September 1999 (10.09.99)
(54) Title: MOUSSE-FORMING SHAMPOO COMPOSITIONS (57) Abstract A mousse-forming cleansing shampoo composition having improved conditioning performance comprising: (A) a foamable concentrate comprising: (i) at least one surfactant; (ii) emulsified particles of a conditioning agent having a particle size of ≤ 1 micron; (iii) a deposition polymer for the emulsified particles; (iv) an aqueous carrier; and (B) an aerosol propellant.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

INTERNATIONAL SEARCH REPORT

Application No

PCT/EP 98/08149

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61K7/50 A61K7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 567 326 A (UNILEVER PLC ;UNILEVER NV (NL)) 27 October 1993 see page 2, line 55 - page 4, line 54 see page 5, line 52 - page 6, line 16 ---	1,5-7
X	WO 96 31188 A (UNILEVER PLC ;UNILEVER NV (NL)) 10 October 1996 see page 5, paragraph 4 - paragraph 5; claims; example 4 ---	1-8
A	WO 96 03969 A (NAT STARCH CHEM INVEST) 15 February 1996 see the whole document ---	1-8
A	GB 2 190 393 A (OREAL) 18 November 1987 see examples --- -/--	1-8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

6 July 1999

Date of mailing of the international search report

13/07/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Couckuyt, P

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 98/08149

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 674 898 A (UNILEVER PLC ;UNILEVER NV (NL)) 4 October 1995 see page 4, line 26; claims -----	1-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

In Application No

PCT/EP 98/08149

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0567326 A	27-10-1993	AT 167801 T	15-07-1998
		AU 3705993 A	28-10-1993
		BR 9301620 A	26-10-1993
		CA 2094483 A	23-10-1993
		DE 69319374 D	06-08-1998
		DE 69319374 T	17-12-1998
		ES 2120480 T	01-11-1998
		JP 6040862 A	15-02-1994
		US 5441730 A	15-08-1995
		US 5580550 A	03-12-1996
		ZA 9302800 A	21-10-1994
WO 9631188 A	10-10-1996	AU 695227 B	06-08-1998
		AU 5499896 A	23-10-1996
		BR 9604872 A	26-05-1998
		CA 2215751 A	10-10-1996
		CN 1185728 A	24-06-1998
		EP 0820266 A	28-01-1998
		JP 10511099 T	27-10-1998
		US 5776444 A	07-07-1998
WO 9603969 A	15-02-1996	US 5478553 A	26-12-1995
		US 5609857 A	11-03-1997
		AU 696302 B	03-09-1998
		AU 3155595 A	04-03-1996
		BR 9508526 A	18-11-1997
		CA 2196595 A	15-02-1996
		EP 0774952 A	28-05-1997
		US 5632977 A	27-05-1997
GB 2190393 A	18-11-1987	LU 86430 A	16-12-1987
		AU 606867 B	21-02-1991
		AU 7299887 A	19-11-1987
		BE 1000998 A	06-06-1989
		CA 1283608 A	30-04-1991
		CH 672593 A	15-12-1989
		DE 3716380 A	19-11-1987
		FR 2598613 A	20-11-1987
		JP 1882679 C	10-11-1994
		JP 6010128 B	09-02-1994
		JP 62277312 A	02-12-1987
		NL 8701175 A	16-12-1987
		US 4880618 A	14-11-1989
EP 0674898 A	04-10-1995	BR 9501289 A	31-10-1995
		CA 2145474 A	01-10-1995
		JP 7277931 A	24-10-1995